



ENVIRONMENTAL PRODUCT INFORMATION

NERA



● Recycled content 51,70%



20kg CO2-eq.
(A1-A3)

MER A


ENVIRONMENTAL PRODUCT INFORMATION

KLÖBER



mer46, 3961, 3510, 3253, 2080, 3150, URBAN

Global warming potential within the product life cycle [GWP; kg CO2-eq.]



standards / certificates

Klöber has been committed to the principles of sustainable corporate governance of the United Nations Global Compact and its principles in terms of human rights, labour, the environment and anti-corruption since 2017.

The life cycle assessment was prepared in accordance with DIN EN 15804.

Contact: nachhaltigkeit@kloeber.com



Features

- 3D mesh backrest
- Arm supports with PP finish
- Tubular steel frame Ø 25 mm, bright chromed
- Fabric: Urban (Camira)
- Suitable for up to 130 kg body weight
- 5 years warranty (see terms and conditions of sale and delivery)

Production

- Covers not glued
- CFC-free PU foam cushion
- Galvanisation with chrome III
- Use of certified upholstery fabrics in accordance with OEKO-TEX Standard 100
- Produced using 100% green electricity
- Produced in accordance with DIN ISO 14001 Environmental management
- Produced in accordance with DIN EN 45001 Occupational safety

Recycled content / recyclable materials

	kg	%
Recycled content	4,66	51,70
	kg	%
Recycling of materials	6,90	76,47
Energy recovery	2,12	23,53

Recyclability

99%

The recycled materials and the recyclability of materials are determined based on data from experts and specialist organisations. When determining recycling values, Klöber uses conservative practice-oriented values and not merely the theoretically possible values. The figures shown include our products' packaging. This fact sheet is checked regularly and may be changed without giving prior notice. The most recent version can be downloaded from our homepage at any time.



Statement

We develop products which bring together first-class quality, design, ergonomics, durability as well as ecological and economic standards in a balanced and unmistakable way – perfectly in line with our customers' needs. To this end, we set high standards for each life phase of the product.

We purchase around two thirds of the steel, aluminium and wood which we require to produce our products in Germany and almost all the rest from Europe, this helps us to avoid long delivery routes whilst, at the same time, boosting the local economy. We use materials which have been tested and assessed with respect to potentially adverse effects on human health and the environment.

REACH Regulation

This product contains no substances as per the candidate list of the REACH Regulation, Annex XIV, above the limit value of 0.1 % mass percent.

Electrical appliance law

WEEE-Reg.-Nr. DE 42358248 Electrical components were registered by Klöber or our suppliers as per the Electrical allpiance law.

Materials

Composition of the materials used for the model:

mer46, 3961, 3510, 3253, 2080, 3150, URBAN

Reference quantity: 1 unit

Metals

	kg	%
Steel	4,536	50,85



Plastics

	kg	%
Polypropylene (PP)	2,780	31,17
PUR foam	0,530	5,94
Polyester fabric	0,434	4,87
Polyester thread	0,122	1,37
Polyamide 6.6 (PA66)	0,003	0,03



Further materials

	kg	%
Fibreglass	0,515	5,77



Total weight (without packaging) 8,92kg


Disclaimer: The material list given may not include all the materials used in this product (e.g. adhesives, coatings, residues etc.).

MERA


ENVIRONMENTAL PRODUCT INFORMATION

KLÖBER

Material cycle



Global warming potential within the product life cycle [GWP; kg CO₂-eq.]



Procurement and transport

It is always in Klöber' interest to purchase resources and production means from nearby partners whenever this is economically viable. Communication is easier, there are no customs duties or currency risks and shorter shipping routes are less harmful for the environment. That's why, our most important supplier country is Germany followed by other European states. The percentage of deliveries from non-European countries is less than 3%. The proximity of the suppliers results in short shipping routes.

Production

Klöber is characterised by its impressive vertical range of manufacture. Key, environmentally relevant processes thus take place in our production facility which are subject to regular certification.

Waste management and recycling

Klöber works exclusively with certified specialist disposal firms which it audits at regular intervals. It has worked closely with a complete disposer since 2013. We recycle paper, cardboard, plastic, glass, wood and metal at all sites. To avoid waste, the rejection rate during the production process is monitored and continually improved.

Creator of the life cycle assessment

Sphera Solutions GmbH, Hauptstraße 111-113, 70771 Leinfelden-Echterdingen

ENVIRONMENTAL PRODUCT INFORMATION



Environmental impacts	Unit	A1-A3	C3	C4	D
GWP Global warming potential	[kg CO ₂ -eq.]	2,03E+01	1,14E+01	7,02E-03	-7,01E+00
ODP Ozone depletion potential	[kg CFC11-eq.]	9,74E-10	1,19E-15	3,86E-17	-6,47E-14
AP Acidification potential	[kg SO ₂ -eq.]	3,61E-02	1,11E-03	4,46E-05	-1,01E-02
EP Eutrophication potential	[kg PO ₄₃ -eq.]	1,00E-02	2,60E-04	5,02E-06	-1,14E-03
POCP Photochemical ozone creation potential	[kg ethene-eq.]	4,47E-03	9,58E-05	3,38E-06	-1,14E-03
ADPE Abiotic depletion potential for non fossil resources	[kg Sb-eq.]	5,53E-06	1,50E-08	7,09E-10	-8,89E-07
ADPF Abiotic depletion potential for fossil resources	[MJ]	3,99E+02	1,40E+00	9,94E-02	-8,73E+01

Resource use	Unit	A1-A3	C3	C4	D
PERE Use of renewable primary energy excluding renewable primary energy resources used as raw materials	[MJ]	6,51E+01	3,35E+00	1,34E-02	-1,86E+01
PERM Use of renewable primary energy resources used as raw materials	[MJ]	3,06E+00	-3,06E+00	0,00E+00	0,00E+00
PERT Total use of renewable primary energy resources	[MJ]	6,82E+01	2,92E-01	1,34E-02	-1,86E+01
PENRE Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials	[MJ]	2,70E+02	1,56E+02	1,03E-01	-1,05E+02
PENRM Use of non renewable primary energy resources used as raw materials	[MJ]	1,55E+02	-1,55E+02	0,00E+00	0,00E+00
PENRT Total use of non renewable primary energy resources	[MJ]	4,25E+02	1,63E+00	1,03E-01	-1,05E+02
SM Use of secondary material	[kg]	3,62E+00	0,00E+00	0,00E+00	0,00E+00
RSF Use of renewable secondary fuels	[MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF Use of non renewable secondary fuels	[MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW Use of net fresh water	[m ³]	6,46E-01	2,48E-02	2,58E-05	-2,45E-02

Output flows and waste categories	Unit	A1-A3	C3	C4	D
HWD Hazardous waste disposed	[kg]	4,34E-07	1,09E-09	1,56E-09	-4,76E-08
NHWD Non hazardous waste disposed	[kg]	3,66E-01	5,09E-02	5,15E-01	-6,75E-02
RWD Radioactive waste disposed	[kg]	8,97E-03	8,92E-05	1,17E-06	-6,62E-03
CRU Components for re-use	[kg]	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MFR Materials for recycling	[kg]	0,00E+00	9,17E-01	0,00E+00	0,00E+00
MER Materials for energy recovery	[kg]	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE Exported electrical energy	[MJ]	0,00E+00	2,30E+01	0,00E+00	0,00E+00
EET Exported thermal energy	[MJ]	0,00E+00	4,09E+01	0,00E+00	0,00E+00

Copyright/party responsible for content: Klöber GmbH, Hauptstrasse 1, 88696 Owingen.
All rights reserved. Content can be changed without prior notice.